

ONBOARD INDICATOR NEEDLE WITH LUMINESCENT LIGHTING

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

[0001] The present Application is a National Stage of Application PCT/EP2004/01837 entitled, "Onboard Indicator Needle with Luminescent Lighting" filed on July 13, 2004 which published under PCT Article 21(2) on January 27, 2005 as WO 2005/008185 A2 in the French language, which claims priority to French Patent Application No. 03/08676 filed on July 16, 2003, the disclosures of which are incorporated herein by reference in their entirety.

BACKGROUND

[0002] The invention relates to the field of onboard indicators with luminous needles for motor vehicle dashboards and more particularly the mounting and the connection of these luminous needles.

[0003] Luminous needles ~~such as these~~ exist on numerous motor vehicle dashboard indicator dials. They are designed to indicate, as a function of their angular swing over a determined sector of the dial, a physical quantity relating to ~~the driving of the vehicle~~.

[0004] The luminous needles may, on the basis of a fixed light source close to their rotational spindle, receive their light by virtue of light guides provided in their hub and be arranged so as to diffuse the light over their length. In this case, in their rotational motion to indicate a physical quantity, the light source remains fixed and there is no problem with its electrical energizing (or ability to receive power). However, this mode of lighting requires a hub of complex design and the brightness of the needle is not optimal.

[0005] Luminous needles may also contain their own light source, which is then energized electrically by conductors provided in the hub. This method eliminates the drawback above, but the electrical link between the two sources is dynamic since the light source turning with the needle and the electrical energizing source ~~necessarily being~~ is fixed on the electronic card of the dashboard, ~~the electrical link between the two sources is necessarily~~ dynamic.

-2-

[0006] The proposal has been contemplated, for example in document U.S. Patent No. 5,797,345, to mount sliding contacts linked to the light source, on the hub of the needle, and fix the contacts linked to the energizing source, in contact with the said-sliding contacts, ~~fixed contacts linked to the energizing source.~~

[0007] This second solution has the drawback however of requiring ~~on the one hand~~ the presence of sliding contacts, contacts which may be always prone to wear by friction and to fouling/mishandling, even to the extent of cutting off the energy supply to the light source. ~~On the other hand~~ Additionally, the complexity of the mounting of the electrical circuits gives rise to a additional not inconsiderable cost considerations.

SUMMARY

[0008] The present invention vehicle dashboard proposes, for this second solution, an improvement aimed at eliminating the presence of any sliding contact while ensuring simple mounting of the needle.

[0009] In one exemplary embodiment, an onboard indicator includes a luminous needle. The indicator is mounted on a dashboard electronic card and the needle comprises an arm rotatable with a light source. The dashboard electronic card is configured to provide an energizing source for the light source and the light source comprises a support composed of flexible material having a first part and second part. The first part is covered with a photophore substance and is configured to be subjected to an electric voltage from the energizing source. The first part is linked electrically by a flexible link formed by the second part of the flexible support and wherein the second part serves as substrate for at least two conducting tracks.

[0010] In another exemplary embodiment, a vehicle dashboard comprises a dashboard electronic card, an indicator mounted with respect to the dashboard electronic card, a needle mounted with respect to the indicator and configured to illuminate. The needle comprises a rotatable arm having a light source and the dashboard electronic card is configured to provide electric power to the light source. A flexible support has a first part and a second part, the first part having a photophore substrate. The first part is flexible and configured to receive an electronic voltage from the dashboard

-2-

electronic card. At least two conductive tracks are coupled to the second part and the first part is configured to electrically link the second part and the dashboard electronic card.

[0011]In yet another exemplary embodiment, is a method of operating a needle of an onboard indicator suitable for a dashboard of a motor vehicle. The needle rotates with respect to the dashboard. The method comprises: providing an electronic card with the electronic card coupled to the onboard indicator; providing a light source, with the light source rotatable and the electronic card configured to power the light source through at least two conductive tracks; providing an electrically conductive support with pins mounted with respect to the electronic card (the pins are pins configured to be in contact with at least one of the two conductive tracks); providing a flexible electrical link between the conductive tracks and the electrically conductive support; and powering the light source from the electronic card through the flexible electrical link.

[0012]For this purpose, the inventionvehicle dashboard relates to an onboard indicator with luminous needle, in which indicator is mounted on a dashboard electronic card, tThe needle comprising comprises an arm movable in rotation with a light source and the electronic card a source for energizing the light source. The indicator is characterized in that the has a light source which comprises a first part of a support of flexible material covered with a photophore substance subjected to an electric voltage from the energizing source to which it is linked electrically by a flexible electrical link (or flexible link) formed by a second part of the insulating flexible support. The second part of the insulating flexible support servesing as substrate for at least two conducting tracks.

[0013]In particular, the second part of the flexible support is attached to at least two pins so that can each be fitted into an electrical contact attached to the electronic card, Eeach pin-being is in contact with one or other of the two conducting tracks.

[0014]When the indicator is activated (or called on to indicate a physical quantity), its-the needle pivoting-pivots about its spindle and, the electrical link unwinds around the hub of the needle. Therefore, the need for aAny sliding contact has thus-been eliminated.

-2-

[0015] The needle ~~thus~~ comprises a minimum of components to be mounted ~~in a minimum space~~ with the space of the vehicle dashboard.

[0016] Preferably ~~also~~, at its end attached to the electronic card, the flexible film is attached to at least two pins that each ~~can each~~ be fitted into an electrical contact ~~attached to the~~ on the electronic card, ~~e~~ Each pin ~~being~~ is in contact with one or other of the two conducting tracks.

[0017] This arrangement allows mounting of the indicator in a single operation by plugging in ~~of the~~ electrical connections of the light source ~~of~~ into the needle with its ~~the~~ energy supply, ~~and mechanics of the spindle of the needle on its drive motor.~~

[0018] Advantageously, the pins are assembled on a support of pins that which can be secured into a housing ~~for thereby~~ retaining the pins support provided in the needle to facilitate mounting.

[0019] Advantageously ~~again~~, the pins support retaining housing and the electrical contacts of the electronic card are arranged so as to enable the pins to be plugged into the contacts, in the mounted position of the indicator, ~~to allow the plugging of the pins into the contacts, and so as, To avoid the colliding of the housing for retaining the pins support with the pins support in the indicator is positioned not to block the operation thereof or hinder the swing of the indicator during operation. operating position of the indicator, to avoid the colliding of the housing for retaining the pins support with the pins support, doing so in order not to block the operation thereof or hinder the swing thereof.~~

[0020] Advantageously still, the pins support and the retaining housing are arranged so as to be detached upon the powering-up of the motor of the indicator.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The invention will be better understood by virtue of the following description of exemplary embodiments of an ~~the~~ onboard indicator ~~according to the invention and of the accompanying drawings accompanying it in which:~~

[0022] —Figure 1 represents a sectional profile view of the needle of the onboard indicator according to the one exemplary embodiment of the invention ~~vehicle dashboard, the needle being in the mounted position;~~

-2-

[0023]—Figure 2 represents a view from below of the needle in the same position, the electronic card and the dial being removed, according to one exemplary embodiment of the vehicle dashboard;

[0024]—Figure 3 represents a perspective view of the pins support according to one exemplary embodiment of the vehicle dashboard;

[0025]—Figure 4 represents a sectional profile view of the needle of the onboard indicator of the ~~invention~~vehicle dashboard, ~~the needle being in the operating position, according to one exemplary embodiment of the vehicle dashboard;~~ and

[0026]—Figure 5 represents a view from below of the needle in the same position as Figure 4 according to one exemplary embodiment of the vehicle dashboard, ~~the electronic card, the flexible film and the dial being removed.~~

DETAILED DESCRIPTION

[0027]With reference to Figure 1, the onboard indicator 1 of the vehicle dashboard comprises a dial 14, made of polycarbonate materials for example, bearing graduations indicative of physical quantities relating to the progress of the vehicle, at In the centre thereof of the onboard indicator ~~and an opening 40 (or orifice) is defined~~ through which there passes a hub 15 attached to a spindle 19 of a motor 20. The motor may be a stepper motor ~~for example a stepper motor~~, mounted on an electronic card 21.

[0028]The hub 15 is extended by a needle 10 running towards the graduations of the dial 14 through an arm 11 ~~completely which is at least partially covered~~ by a transparent fairing 12 (or smooth surface). The stepper motor 20 is arranged so as to make the needle pivot as a function of the physical quantity to be displayed on the dial.

[0029]An adhesive is utilized B~~etween~~ the visible part of the arm 11 and the fairing 12 ~~is glued and applied~~, onto the ~~arm, arm in which case~~ a first part 30' of a support is partially covered with a layer of photophore material, In one exemplary embodiment the material is for example an electroluminescent ink applied, over a determined area so as to form the pointer ~~(not represented)~~ of the needle.

-2-

[0030] According to an exemplary embodiment of the invention on board indicator 1, ~~the~~ includes a support 30 which runs beyond the arm 11 of the needle 10 through a second band-shaped part 30" extending along the hub 15, ~~but~~ The support 30 is free, to pass through the dial 14 via the opening 40, then and travel around the hub 15 along an 'S' shaped spiral S surrounding the said hub, ~~under underneath the dial, of a sufficient length specified later.~~

[0031] ~~To dial.~~ To do accomplish this, the support 30 is folded over on itself at 90°, at approximately the height of the hub, forming a fold 45.

[0031] The support 30 is electrically insulating, ~~in its~~ The second part of the support ~~it~~ comprises two parallel conducting tracks 31 and 32 linked to either side of the pointer so as to energize it electrically in a suitable manner, and to enable the pointer to extending without interruption up to its free end. On the first part 30' of the support 30 these two conducting tracks act as electrodes over the entire useful length of the needle or at least its visible part and ~~provide for enables~~ the excitation of the electroluminescent ink. One of the tracks 31 ~~is in abuts~~ contact 41 with a pin 23 attached to the support 30, and the other track 32 abuts contact 42 with another pin 24 which is also attached to the latter support 30. The contacts 41 and 42 are fairly distant from the support 30 so as to provide for plug-in mounting, ~~which will be explained further on.~~ In one exemplary embodiment, as illustrated in

[0033] Figure 2, ~~shows the~~ 'S' shaped spiral S ~~is~~ formed by the band 30" around the hub 15 and the layout of the pins (23 and 24) attached to its free end.

[0034] As the band 30" is flexible, the pins 23, 24 are held in parallel with respect to one another ~~in the manner of the pins of an ordinary electric plug by means of a pins support 25, as is shown~~ illustrated in Figure 3.

[0032] The pin support 25 comprises a central spigot 26, and two equidistant holes (or apertures) 43 and 44 in which the ends 33 and 34 of the pins 23 and 24 are inserted. The pins 23, 24 run out of the support 25 away from the central spigot 26.

[0033] The band 30" is glued to the pins 23 and 24, ~~and,~~ In one exemplary embodiment, in order to avoid an electrical short-circuit, insulating bushings 51 and 52 have been disposed on the pins 23 and 24 to insulate the pin 23

-2-

from the track 32 and to insulate ~~the~~ pin 24 from the track 31. Thus the pin 23 is in electrical contact at 41 only with the track 31 and the pin 24 is in electrical contact at 42 only with the track 32.

[0034] Under the needle 10, a spigot 16 has been provided in such a way as to be fairly close to the hub 15 so as to pass into the opening 40, in which a housing 17 retaining the support 25 of the pins 23 and 24 has been made.

[0035] The spigot 16 of the needle 10 is of such a length that, when the spigot 26 of the pin support 25 is engaged in the housing 17, the pins 23 and 24 can be plugged into the electrical contacts 22 attached to the electronic card 21. The housing 17 is arranged, as ~~may be seen~~ in Figure 5, so as to retain the spigot 26 by lateral snap-fastening.

[0036] When, in a mounted position of the needle, the spigots 16 and 26 are aligned and the pins are plugged into the contacts 22, the needle is situated outside of its operating range on the dial.

[0039] Consequently, the length of the band 30" is sufficient to allow the needle to pivot not only over the whole entirety of the said operating range, but also, beyond, ~~up to~~ the mounted position of the needle ~~defined previously~~.

[0037] During normal operation of the indicator 1, ~~with reference to as illustrated in the exemplary embodiment of~~ Figure 4, the needle 10 is in an operating position situated somewhere in a sector determined by its swing about its spindle 19, in general, the swing covers ~~by an angle of 180° or more, but less than a complete revolution.~~ In this case, the support 25 of the pins 23, 24, which are plugged into the contacts 22, is not situated in the said sector. ~~It~~ The support 25 remains out of reach of the spigot 16 of the needle 10 ~~which is thereby~~ not hindered in its indication motion.

[0038] For the mounting of the needle, the spigot 26 of the support 25 of the pins 23, 24 is engaged into the housing 17 and the pins are plugged into the contacts 22 ~~at the same time as~~ Simultaneously ~~the~~ hub 15 is plugged into the spindle 19 of the motor 20. The needle is then placed in a mounted position as in Figure 1, outside of the sector determined by its sweep while operating.

-2-

[0039] For placement in the operating position, the needle 10 is forced, to turn, manually or automatically by starting up the motor 20, to turn so as to bring it the needle into the sector. Through this action, the spigot 26 is forced to leave the spigot 16.

[0040] During operation, the electrodes of the first part 30' of the support provide for the excitation of the photophore material which becomes luminous. Regardless of the position of the needle, the energizing of the first part is provided for by the electrodes on the second part which by virtue of the flexibility of the support 30" follow the motion thereof while remaining connected to the source of current.

[0041] It should be understood that the construction and arrangement of the elements of the onboard indicator in the exemplary embodiments are illustrative only. Although several embodiments of the onboard indicator have been described in detail in this disclosure, many modifications are possible without materially departing from the novel teachings and advantages of the subject matter recited in the claims. Accordingly, all such modifications are intended to be included within the scope of the present onboard indicator as defined in the appended claims. Unless specifically otherwise noted, the claims reciting a single particular element also encompass a plurality of such particular elements. Moreover, claims reciting that one element is coupled to another should be interpreted to mean that the elements are selectively coupled to each other and may be uncoupled or disconnected at any point. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. In the claims, any means-plus-function clause is intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Other substitutions, modifications, changes and/or omissions may be made in the design, operating conditions and arrangement of the preferred and other exemplary embodiments without departing from the spirit of the present invention as expressed in the appended claims.

-2-

CLAIMS

1. ~~Onboard indicator (1) with luminous needle (10), which indicator is mounted on a dashboard electronic card (21), the needle comprising an arm movable in rotation with a light source (13) and the card a source (22) for energizing the light source, characterized in that the light source comprises a support of flexible material (30) with a first part (30') covered with a photophore substance (13) subjected to an electric voltage from the energizing source to which it is linked electrically by a flexible electrical link (30, 31, 32) formed by a second part (30'') of the insulating flexible support (30) serving as substrate for at least two conducting tracks (31, 32).~~
2. ~~Indicator according to Claim 1, in which the second part (30'') of the flexible support (30) is attached to at least two pins (23, 24) that can each be fitted into an electrical contact (22) attached to the electronic card (21), each pin being in contact (41, 42) with one (31) or other (32) of the two conducting tracks.~~
3. ~~Indicator according to Claim 2, in which the pins (23, 24) are assembled on a support (25) of pins that can be secured (26) into a housing (17) for retaining the pins support provided in the needle (10).~~
4. ~~Indicator according to Claim 3, in which the pins support retaining housing (17) and the electrical contacts (22) of the electronic card (21) are arranged so as, in the mounted position of the needle, to allow the plugging of the pins (23, 24) into the contacts (22), and so as, in the operating position of the needle, to avoid the colliding of the housing (16, 17) for retaining the pins support (25) with the pins support (25).~~
5. ~~Indicator according to one of Claims 3 and 4, in which the pins support (25) and the retaining housing (17) are arranged so as to be detached upon the powering up of the motor (20) of the indicator.~~

ABSTRACT

~~The invention vehicle dashboard~~ pertains to an onboard indicator (1) with luminous needle (10), ~~which~~ The indicator is mounted on a dashboard electronic card (21), ~~and the needle comprising~~ comprises an arm movable in rotation with a light source (13) ~~and~~ The card is a source (22) ~~for of~~ energizing the light source. ~~It is characterized in that~~ The light source comprises a support made of flexible material (30) with a first part (30') covered with a photophore substance (13) ~~and~~ subjected to an electric voltage from the energizing source. The energizing source to which it is linked electrically by a flexible electrical link (30, 31, 32) which is formed by a second part (30") of the insulating flexible support (30), serving which serves as substrate for at least two conducting tracks, (31, 32).

~~The solution of the invention makes it possible to produce a very flat indicator with a minimum of components.~~

~~Figure for the abstract: Figure 1~~